



QTY.	PIPE SIZE NPS	A (IN)	PRESSURE* (PSI)	NOTES
	2"			
	2-1/2"			
	3"			
	4"			
	5"			
	6"			
	8"			
	10"			
	12"			
	14"			

\* FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY PRESSURE SHOWN AT 70°F TIMES CORRECTION FACTOR OF REQUIRED TEMP.

TEMP °F	FACTOR
70	1.0
150	.97
200	.94
250	.92
300	.88
350	.86
400	.83
450	.81
500	.78
600	.77

MAX. PERMANENT OFFSET FROM  $\epsilon$    
 MAX INTERMITTENT OFFSET FROM  $\epsilon$

CUSTOMER: \_\_\_\_\_

PROJECT: \_\_\_\_\_

ENGINEER: \_\_\_\_\_

PURCHASE ORDER: \_\_\_\_\_

REV.	DATE
5331 Quam Ave., N.E. St. Michael, MN 55376 TEL:763-201-2151 FAX:763-201-2134 www.engineeredflex.com	
<b>STAINLESS STEEL BRAIDED CONNECTOR</b>	
DRAWN BY: AD	DATE: 10/12/2010
APPROVED:	DATE:
SCALE: NONE	DRAWING NUMBER: