

THE EXPANSION JOINT IS DESIGNED FOR AXIAL MOVEMENT ONLY.
PIPE MUST BE PROPERLY GUIDED AND ANCHORED PER THE
RECOMMENDATIONS OF THE EXPANSION JOINT MANUFACTURERS ASSOCIATION.

QTY.	SIZE		THREAD/	FLANGED	_		
	INCH.	MM.	WELD END A1	A2	В	С	NOTES
	3/4"	20	12-3/4"	13-3/8"	2-3/8"	1.05"	
	1"	25	13-1/4"	13-7/8"	2-1/2"	1.31"	
	1-1/4"	32	13-1/4"	13-7/8"	3"	1.66"	
	1-1/2"	38	14-5/8"	15-1/4"	3-1/2"	1.90"	
	2"	50	14-5/8"	15-1/4"	4"	2.37"	
	2-1/2"	65	16"	16-5/8"	5"	2.87"	
	3"	80	16"	16-5/8"	5-1/2"	2.87"	
	4"	100	16-3/8"	17"	6-5/8"	4.50"	

TEMP	750° F (399°)					
PRESS	175 PSI (1206	K PA (G))				
TEST PRESS	250 PSI (1809	K PA (G))				
AXIAL MOVEMENT1/2" EXTENSION, (13 MM)						
	2" COMPRESS	SION, (50MM)				
CUSTOMER:						
PROJECT:						
ENGINEER:						
PURCHASE ORDER:		LEAD FR				

REV.	DATE					
St. Michael, MN 55376 TEL:763-201-2151 FAX:763-201-2134 www.engineeredflex.com COMPENSATORS H SERIES						
DRAWN BY:	AD	DATE: 03/10/2011				
APPROVED	:	DATE:				
scale: NONE	DRAWING NUMBER:					