



FACTORY INSULATION IS A HYDROUS CALCIUM SILICATE, MAXIMUM TEMPERATURE 1200°F, K FACTOR 0.31 @ 75°F. COMPRESSIBILITY 100 PSI, VAPOR BARRIER IS A PART OF THE INSULATION.

NO. SIZE	WEIGHT (APPROX.) LBS. EACH	DIMENSIONS IN INCHES						
		H	R	W	Y	B	C	L
06	10	7 5/8	4 1/2	8 1/8	5 1/8	5/8	1 3/4	3
08	13	9 1/4	5 1/4	10 1/8	6 1/8	5/8	1 3/4	3
10	20	11 5/8	6 1/4	12 1/8	7	5/8	2 3/4	4
12	25	13 3/8	7	14 1/8	8 1/4	5/8	2 3/4	4
14	40	15 1/8	7 7/8	16 1/8	9 7/8	3/4	4	6
16	45	17	8 7/8	18 1/8	10 7/8	3/4	4	6
18	55	18 3/4	9 3/4	20 1/8	11 7/8	3/4	4	6
20	65	21	10 7/8	22 1/8	11 3/4	3/4	4	6
22	95	23 1/8	12 1/8	24 1/8	14 1/2	7/8	6	8
24	100	25	13	26 1/8	15 1/2	7/8	6	8
26	120	27 3/4	14 3/4	28 1/8	17 1/8	1 1/8	6	8
30	150	31 1/2	16 1/2	32 1/8	19 1/4	1 1/8	6	8

- NOTE:**
1. ALL FRACTIONS TO NEAREST 1/8th INCH.
  2. BODY SIZE 14" & UP SUPPLIED WITH 4 BOLTS.



5331 Quam Ave, N.E.  
 St. Michael, MN 55376  
 TEL: 763-201-2151  
 FAX: 763-201-2134  
 www.engineeredflex.com

**PRE-INSULATED SERIES GUIDE**

Approved By:	Drawn By:	Date:
.	E.RIVERA	8/13/00
Scale:	Lateral Movement:	Tolerance:
NONE	.	.

Material:	ASTM A-36 CARBON STEEL
Finish:	BLACK PAINT
Drawing Number:	Revision:
55INS0001	.