



QTY.	PIPE SIZE NPS	A (IN)	PRESSURE* (PSI)	NOTES	Lateral Offset
	2"	9	475		±1/8"
	2-1/2"	9	350		±1/8"
	3"	9	300		±1/8"
	4"	9	250		±1/8"
	5"	11	175		±1/8"
	6"	11	165		±1/8"
	8"	12	234		±1/8"
	10"	13	230		±1/8"
	12"	14	161		±1/8"
	14"	14	119		±1/8"

*FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY PRESSURE SHOWN AT 70°F TIMES CORRECTION FACTOR OF REQUIRED TEMP.

TEMP °F	FACTOR
70	1.0
150	.95
200	.91
250	.88
300	.85
350	.81
400	.78
450	.77
500	.77
600	.76



NOTES:

NSF 372 - LEAD FREE: The wetted surface of this product contacted by water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards where applicable, requiring reduced lead content.

REV. DRAWN BY: AM Date: 1/11/2019



5331 Quam Ave NE
St. Michael, MN 55376
Phone: 763-201-2151
Fax: 763-201-2134
Email: sales@engineeredflex.com

Customer:	
Project:	
Style:	STAINLESS STEEL FLEX CONNECTOR
SCALE:	DRAWING NUMBER:
NONE	