



QTY.	PIPE SIZE NPS	A (IN)	PRESSURE* (PSI)	NOTES	MAX INTERMITTENT OFFSET FROM ⌀
	1/2"	6-1/2"	1200		±1/8"
	3/4"	7"	1034		±1/8"
	1"	8"	796		±1/8"
	1-1/4"	8-1/2"	600		±1/8"
	1-1/2"	9"	551		±1/8"
	2"	10-1/2"	557		±1/8"
	2-1/2"	12"	387		±1/8"



*FOR SAFE WORKING PRESSURE ABOVE 70°F,
MULTIPLY PRESSURE SHOWN AT 70°F TIMES
CORRECTION FACTOR OF REQUIRED TEMP.

TEMP °F	FACTOR
70	1.0
150	.95
200	.91
250	.88
300	.85
350	.81
400	.78
450	.77
500	.77
600	.76

NOTES:

NSF 372 - LEAD FREE: The wetted surface of this product contacted by water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards where applicable, requiring reduced lead content.

REV. DRAWN BY: AM Date: 1/22/2019



5331 Quam Ave NE
St. Michael, MN 55376
Phone: 763-201-2151
Fax: 763-201-2134
Email: sales@engineeredflex.com

Customer:	
Project:	
Style:	STAINLESS STEEL FLEX CONNECTOR
SCALE:	DRAWING NUMBER:
NONE	