



QTY.	PIPE SIZE NPS		A (IN)	PRESSURE* (PSI)	NOTES	MAX INTERMITTENT OFFSET FROM ℄
	LARGER	SMALLER				
	2-1/2"	2"	13	387		±1/8"
	3"	2"	13	316		±1/8"
	4"	2"	13	232		±1/8"
	3"	2-1/2"	13	316		±1/8"
	4"	2-1/2"	13	232		±1/8"
	5"	2-1/2"	16	191		±1/8"
	4"	3"	13	232		±1/8"
	5"	3"	16	191		±1/8"
	6"	3"	17	165		±1/8"
	5"	4"	16	191		±1/8"
	6"	4"	17	165		±1/8"
	8"	4"	18	235		±1/8"
	6"	5"	17	165		±1/8"
	8"	5"	18	235		±1/8"
	8"	6"	18	235		±1/8"
	10"	6"	18	230		±1/8"
	10"	8"	18	230		±1/8"
	12"	10"	20	160		±1/8"

*FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY PRESSURE SHOWN AT 70°F TIMES CORRECTION FACTOR OF REQUIRED TEMP.

TEMP °F	FACTOR
70	1.0
150	.95
200	.91
250	.88
300	.85
350	.81
400	.78
450	.77
500	.77
600	.76

NOTES:

NSF 372 - LEAD FREE: The wetted surface of this product contacted by water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards where applicable, requiring reduced lead content.

REV. DRAWN BY: CL Date: 4/30/2019



5331 Quam Ave NE
St. Michael, MN 55376
Phone: 763-201-2151
Fax: 763-201-2134
Email: sales@engineeredflex.com

Customer:	
Project:	
Style:	STAINLESS STEEL FLEX CONNECTOR
SCALE:	DRAWING NUMBER:
NONE	